


Curve saldate 3D 90° ISO

Norme: EN10253 - EN 10254

Materiale: Aisi 304L EN 1.4307 - Aisi 316L EN 1.4404



ACA9SG



DN	DN inch	De mm	R mm	Peso (Kg)						
				1,5 mm	2,00 mm	2,5 mm	3,00 mm	4,00 mm	5,00 mm	6,00 mm
8	1/4"	13,5	20,0	0,014	0,018	-	-	-	-	-
10	3/8"	17,2	28,5	0,026	0,034	-	-	-	-	-
15	1/2"	21,3	31,8	0,037	0,048	-	0,069	-	-	-
20	3/4"	26,9	28,5	0,043	0,056	-	0,080	-	-	-
25	1"	33,7	38,0	0,072	0,095	-	0,138	-	-	-
32	1 1/4"	42,4	47,6	0,115	0,151	-	0,221	-	-	-
40	1 1/2"	48,3	57,1	0,158	0,208	-	0,305	-	-	-
50	2"	60,3	76,2	0,264	0,349	-	0,515	-	-	-
65	2 1/2"	76,1	96,0	0,422	0,559	-	0,828	-	-	-
80	3"	88,9	114,5	0,590	0,782	-	1,160	1,529	-	-
90	3 1/2"	101,6	133,5	-	1,045	-	1,552	2,042	-	-
100	4"	114,3	152,5	-	1,347	-	2,002	2,645	-	-
125	5"	139,7	191,0	-	2,068	-	3,079	4,076	-	-
150	6"	168,3	229,0	-	2,994	-	4,464	5,917	-	-
200	8"	219,1	305,0	-	5,206	-	7,773	10,317	-	-
250	10"	273,0	381,0	-	8,118	-	12,132	16,117	-	-
300	12"	323,9	457,0	-	11,566	-	17,296	22,989	-	-
350	14"	355,6	534,0	-	-	-	22,206	29,525	-	-
400	16"	406,4	610,0	-	-	-	29,022	38,600	-	-
450	18"	457,2	685,0	-	-	-	36,747	48,889	-	-
500	20"	508,0	685,0	-	-	-	45,384	60,392	-	-
600	24"	609,6	914,0	-	-	-	65,389	87,041	-	-
700	28"	711,2	1070,0	-	-	-	-	118,993	148,530	177,984
800	32"	812,8	1220,0	-	-	-	-	155,165	193,717	232,173
900	36"	914,4	1372,0	-	-	-	-	196,418	245,252	293,979
1000	40"	1016,0	1525,0	-	-	-	-	242,686	303,057	363,309